



TIF RX-1A TIF XP-1A Refrigerant Leak Detector

- Microprocessor controlled circuit with Advanced Digital Signal Processing, monitors the sensing tip up to 2000 times per second
- Detects all halogenated refrigerants
- Variable frequency audible alarm 40 cm (14") Flexible stainless probe with Teflon™ liner
- Rubber cushion grip
- Constant power indication
- Power supply: 3 V DC, two "C" cell alkaline batteries (included)
- Sensing tip life: approx. 20 hours (two tips included)
- Operating temp: -20° to 52° C
- Blow molded carrying case included, optional holster
- Certified to SAE J1627
- UL Classified & CE approved
- 2 years warranty

Replacement Parts (supplied with product)	Part Number
Hard Carrying Case	TIF XP-4A
Cover for battery compartment	TIF XP-5A

Optional Accessories	Part Number
Maintenance Kit (3 Tips with protectors)	TIF XP-2

Specifications	TIF RX-1A	TIF XP-1A
Ultimate Sensitivity	< 7 gr/yr (0,25 oz/yr)	< 3 gr/yr (0,1 oz/yr)
True Mechanical Pump	Yes	Yes
Visual Leak Indication Levels	6 (single color)	18 (tri-color)
Sensitivity Levels	2	7
One Touch Reset and Keypad Controls	Yes	Yes
Mute Button	n/a	Yes
Battery Test	n/a	True voltage indication
Battery Life	Approx. 30 hrs.	Approx. 30 hrs.