


**TABLE 6: General characteristics of unions**

	Catalogue Number	Item Position	Connections			PS [bar]	Dimensions [mm]					Wrench torque min / max [Nm]	Weight [g]
			SAE Flare	ODS			L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>4</sub>	Ch		
				Ø [in.]	Ø [mm]								
Flare / ODS adapters													
 <p>POS.1</p>	9901/X11	1	1/4"	-	6	120	-	-	16	12,5	17	11 / 14	274
		2					21	3,5	-	-	-	-	
		3					-						
	9901/X12	1	3/8"	-	10		-	-	18,5	14,7	22	20 / 25	393
		2					23,5	4	-	-	-	-	
		3					-						
	9901/X13	1	1/2"	-	12		-	-	21	17	27	34 / 47	672
		2					26	4,5	-	-	-	-	
		3					-						
	9901/X14	1	5/8"	5/8"	16		-	-	22,5	18	30	54 / 75	511
		2					27,5	5	-	-	-	-	
		3					-						
9901/X15	1	3/4"	-	18	-	-	25	20	36	68 / 71	806		
	2				30	5	-	-	-	-			
	3				-								
9901/X16	1	1/4"	1/4"	-	-	-	16	12,5	17	11 / 14	274		
	2				21	3,5	-	-	-	-			
	3				-								
9901/X17	1	3/8"	3/8"	-	-	-	18,5	14,7	22	20 / 25	383		
	2				23,5	4	-	-	-	-			
	3				-								
9901/X18	1	1/2"	1/2"	-	-	-	21	17	27	34 / 47	672		
	2				26	4,5	-	-	-	-			
	3				-								
9901/X19	1	3/4"	3/4"	-	-	-	25	20	36	68 / 71	806		
	2				30	5	-	-	-	-			
	3				-								

